Indoor Sunbrite Window LED Displays

Alpha-American Programmable Signs





Message Capabilities

- Up to 19 System Fonts including Bold Fonts available
- Capability to Add Custom Fonts
- Up to 48 In/Out Message Transition Modes
- Shuffle Display Modes Randomly
- 7 Message Speeds
- Pause Periods from 0 Seconds to 160 Minutes
- Time and date formats built in
- Scroll Display Mode for Long, Continuous Messages (Ticker)
- Pre-load and Automatically Schedule Thousands of Messages
- Count-Up ("Days Since Lost Time Accident") and Count-Down ("Days Until Christmas")

Standard Features

- 1.5" to 9.0" Characters
- 1024k Flash Memory
- 128 K Ram Memory
- 32-Bit CPU
- 70° degree Viewing Angle
- 0.3" Pitch
- Aluminum Enclosure

- RS232, RS485, USB 2.0 and Ethernet Communication
- 120 VAC, Available 12 VDC or 12-28 VDC Power Supply
- Programmable via: Handheld Remote, Visions Play Software or our Advanced Display Protocol
- RSS feed capability included with Visions Play Software and Internet Access
- Internet Access • ETL Certified to UL48-2012 and CAN/CSA C22.2 No.207-M89
- Hanging, Sitting or Wall Mount Options based on Model.

Additional Options

- NEMA 4x Enclosure
- Handheld Remote, Visions Play Software, 1-ft. RJ22 to RJ11 Cable
- Wireless Connection





PROGRAMMABLE SIGNS ALPHA-AMERICAN.COM CO

COMMUNICATING AT THE SPEED OF LIGHT

800-223-4636 or 858-273-3036 ALPHA-AMERICAN.COM

ALPHA-AMERICAN DISPLAY

Indoor Sunbrite Window LED Displays

Alpha-American Programmable Signs

NEMA-1 Aluminum

file, time zone and date display

Standard Specifications

Configuration

Temperature Rating

Estimated LED Lifetime

Cabinet Construction

Communication **Full Load Watts**

Pixel Pitch

Voltage

Standard

Brightness

Viewing Angle Graphic Capability

ications	Physical	2080-WD			2160-WD			
Enhanced Version with Ethernet	Available Colors	Red, Yellow, Green, Blue, White			Red, Yellow, Green, Blue, White			
	Display Pixels	7 (h) x 80 (w)		7 (h) x 160 (w)				
0.3" (1.5" minimum character height)	Cabinet Height	4"			4"			
120 VAC	Cabinet Width	26"		50"				
0-45°C (32-113°F)	Cabinet Depth	2"		2"				
RS232, RS485, Ethernet, USB	Display Weight	4.4 lbs.		8.8 lbs.				
15-100 Watts	Power Consumption	15 watts maximum		25 watts maximum				
100,000 hours								
1,000 NITs		Lines	Character Height	# of Characters	Lines	Character Height	# of Characters	
70°		1	-		1			
ASCII characters, graphic files, string		1	1.5"	16	1	1.5"	32	

13

1

2.1"

26

Physical	4096-WD	4128-WD	4192-WD	4256-WD
Available Colors	Red Only	Red, Yellow, Green, Blue, White, Full	Red, Yellow, Green, Blue, White, Ful	Red, Yellow, Green, Blue, White, Full
Display Pixels	16 (h) x 96 (w)	16 (h) x 128 (w)	16 (h) x 192 (w)	16 (h) x 256 (w)
Cabinet Height	6.2"	6.2"	6.2"	6.2"
Cabinet Width	31.2"	40.8″	60"	79.2"
Cabinet Depth	3.25"	3.25"	3.25"	3.25"
Display Weight	8.8 lbs.	11.7 lbs.	16.5 lbs.	24 lbs.
Power Consumption	18 watts maximum	25 watts maximum	40 watts maximum	40 watts maximum

1

2.1"

Display	Lines	Character Height	# of Characters	Lines	Character Height	# of Characters	Lines	Character Height	# of Characters		Character Height	# of Characters
	2	1.5"	19	2	1.5"	25	2	1.5"	32	2	1.5"	38
	2	2.1"	16	2	2.1"	21	2	2.1"	26	2	2.1"	32
	1	4.2"	12	1	4.2"	16	1	4.2"	20	1	4.2"	24
	1	4.8″	10	1	4.8″	14	1	4.8″	17	1	4.8″	21

Physical	9128-WD	9192-WD
Available Colors	Red, Yellow, Green, Blue, White	Red, Yellow, Green, Blue, White
Display Pixels	32 (h) x 128 (w)	32 (h) x 192 (w)
Cabinet Height	11.6"	11.6"
Cabinet Width	40.8"	60"
Cabinet Depth	4.25"	4.25"
Display Weight	26.4 lbs.	35.2 lbs.
Power Consumption	60 watts maximum	100 watts maximum

Display

32 (h) x 128 (w)	32 (h) x 192 (w)					
11.6"	11.6"					
40.8"	60"					
4.25"	4.25"					
26.4 lbs.	35.2 lbs.					
60 watts maximum	100 watts maximum					
Character # of Lines Height Characters	Character # of Lines Height Characters					

Lines	Height	Characters	Lines	Heig
5	1.5"	25	5	1.5"
4	2.1"	21	4	2.1"
2	4.2"	16	2	4.2"
1	4.8″	14	1	4.8″



ALPHA-AMERICAN.COM

COMMUNICATING AT THE SPEED OF LIGHT

800-223-4636 or 858-273-3036

ALPHA-AMERICAN.COM